






PH369 - DEFENDER



- Anwendung** Berstschutzschläuche sind weit verbreiteter in der Baumaschinenindustrie und Anlagenbau, um den Verschleiß der Hydraulikschläuche und Verletzungen von Menschen durch das Platzen von Hydraulikschläuchen zu vermeiden.
- Beschreibung** Die Defender Schutzhülle besteht aus einem leistungsstarken Nylongewebe, um Abrieb und Verletzungen zu vermeiden. Die spezielle Webart gibt eine außergewöhnlich glatte Innenwand, in dem sich der Hydraulikschlauch frei bewegen kann, um Verschleiß vorzubeugen. Das Gewebe ist ideal zum Schutz von Mensch, Umwelt und Maschine gegen mögliche Leckagen, da diese austretendes Öl zurückhält.
- Material** Polyamid - PH369N
Polyester - PH369P
Andere Materialien auf Anfrage erhältlich (Mindestmengen anfragen)
- Farbe** Schwarz
- Prüfungen** RoHS ; MSHA IC-359/1, UV und Flammresistent
- Temperatur** -50°C + 125°C (-58°F + 256 °F)

PRODUCT CODE	 ID	 THICKNESS	 FLAT WIDTH	 Colour	 METERS PER BOX
	mm	mm	(+/- 1 mm)		m
PH369-017	17	0,8	30	Black	50
PH369-020	20	0,8	36	Black	50
PH369-023	23	0,8	40	Black	50
PH369-025	25	0,8	43	Black	50
PH369-027	27	0,8	45	Black	50
PH369-031	31	0,8	52	Black	50
PH369-033	33	0,8	55	Black	50
PH369-036	36	0,8	60	Black	50
PH369-040	40	0,8	66	Black	50
PH369-044	44	0,8	74	Black	50
PH369-047	47	0,8	77	Black	50
PH369-053	53	0,8	86	Black	50
PH369-055	55	0,8	90	Black	50
PH369-060	60	0,8	98	Black	50
PH369-066	66	0,8	106	Black	50
PH369-073	73	0,8	118	Black	50
PH369-078	78	0,8	126	Black	50
PH369-085	85	0,8	136	Black	50
PH369-093	93	0,8	150	Black	50
PH369-112	112	0,8	178	Black	50

EXITFLEX - brand of Polyhose

Polyhose Germany GmbH
Am Keuper 16
90475 Nürnberg
Deutschland/Germany



HRB 13931 Amtsgericht Nürnberg
USt-ID: DE 812012103
Geschäftsführer: Roland Theml

Raiffeisenbank Altdorf-Feucht
IBAN: DE18 7606 9440 0000 3337 60
BIC: GENODEF1FEC
Konto: 333760 BLZ 760 694 40

Tel. +49 91 28 / 7 21 32 - 40
Fax +49 91 28 / 7 21 32 - 45
Web www.polyhose.de
Mail phde.info@polyhose.com

Application It widely used in the mining industry to protect the hydraulic hose for wear resistance and avoid people get hurt due to high pressure liquid spray.

Description Protective sleeve consists of nylon tublar sleeve uniquely designed to prevent abrasion which could wear through the sleeve this weave gives an exceptionally smooth interior wall, allowing the rubber hose to move freely inside the sleeve without internal abrasion issue and ideal for protecting people, environment and machinery against any possible hydraulic hose oil leakage or spill






Material For Nylon - PH369N,
For Polyester - PH369P,
Special Material available on request.

Color Black

Approval RoHS ; MSHA IC-359/1 ; UV and Flame resistant

Working Temperatur -50°C + 125°C (-58°F + 256 °F)



PRODUCT CODE	 ID	 THICKNESS	 FLAT WIDTH	 Colour	 METERS PER BOX
	mm	mm	(+/- 1 mm)		m
PH369-017	17	0,8	30	Black	50
PH369-020	20	0,8	36	Black	50
PH369-023	23	0,8	40	Black	50
PH369-025	25	0,8	43	Black	50
PH369-027	27	0,8	45	Black	50
PH369-031	31	0,8	52	Black	50
PH369-033	33	0,8	55	Black	50
PH369-036	36	0,8	60	Black	50
PH369-040	40	0,8	66	Black	50
PH369-044	44	0,8	74	Black	50
PH369-047	47	0,8	77	Black	50
PH369-053	53	0,8	86	Black	50
PH369-055	55	0,8	90	Black	50
PH369-060	60	0,8	98	Black	50
PH369-066	66	0,8	106	Black	50
PH369-073	73	0,8	118	Black	50
PH369-078	78	0,8	126	Black	50
PH369-085	85	0,8	136	Black	50
PH369-093	93	0,8	150	Black	50
PH369-112	112	0,8	178	Black	50

EXITFLEX - brand of Polyhose

Polyhose Germany GmbH
Am Keuper 16
90475 Nürnberg
Deutschland/Germany



HRB 13931 Amtsgericht Nürnberg
USt-ID: DE 812012103
Geschäftsführer: Roland Theml

Raiffeisenbank Altdorf-Feucht
IBAN: DE18 7606 9440 0000 3337 60
BIC: GENODEF1FEC
Konto: 333760 BLZ 760 694 40

Tel. +49 91 28 / 7 21 32 - 40
Fax +49 91 28 / 7 21 32 - 45
Web www.polyhose.de
Mail phde.info@polyhose.com